

SIDDHI VINAYAK CONSTRUCTION CHEMICAL PVT. LTD.

SUPER TILES ADHESIVE



About

Being an unparallel manufacturer, exporter and supplier, we are offering Liquid Super Tile Adhesive to the clients. The provided adhesive is used to fix and seal the mortars, tiles, marbles and other building materials to the horizontal surfaces. Available in different packaging options to suit the specific needs of clients, the offered adhesive is processed by our seasoned professionals by utilizing optimum quality chemicals and pioneering methodology. Furthermore, we are offering this Liquid Super Tile Adhesive to the clients at pocket ECO friendly prices, compare to other powder tiles adhesive.

Description

Siddhi Vinayak Super Tile Adhesive is a liquid form, Super Tile Adhesive is specially formulated to suit most tiles including ceramic, Granite, Porcelain, Mosaics, fully vitrified and natural stone (excluding moisture sensitive stone). Super Tile Adhesive is suitable for use over many different surfaces including timber (indoors) as well as fibercement sheets, Concrete and plasterboard where surfaces are subject to thermal and shrinkage movement. Super Tiles Adhesive can be used indoors (including showers) and outdoors provided there is no standing water and there is a sufficient fall achieved in installation for water runoff.

Advantages

Super Tile Adhesive acts as the cost-effective solution for making tiles water protected. Useful for enhancing tonsilitis level and adhesive properties of mortars Convenient to apply and Eco-friendly content.

- Liquid Super Tile Adhesive water proofs the tiled area.
- Super Tiles Adhesive Improves adhesion and tensile strength of mortars.
- Super Tile Adhesive is economical.
- Super Tile Adhesive Easy to use.
- Super Tile Sdhesive is a Non-toxic

Primary use

Siddhi Vinayak Super Tile Adhesive is used for attaching ceramic tiles on mosaic or concrete flooring.

- Super Tile Adhesive is also effective in affixing granite slab on concrete flooring and for installation of marble slabs on flooring.
- Super Tile Adhesive useful to set up wall skirting perfect for affixing ceramic and glazed tiles, granite on flooring and walls.

Preparation For Usage & Dosage

The Normal Recommended Dosage For Liquid Super Tile Adhesive Is Between 2.0% To 3.0% By Weight Of Cementitious Material. The Optimal Dosage Should Always Be Determined By Trials Using Specific Materials And Conditions That Will Be Experienced In Use. You Should Also Stir Well Before Use.

We Would Prefere Two Type Of Mixing Ratio

For Wall Area:- In Case Affixing Tiles, Granite & Marble In Wall Area So Prefere This Mix Ratio

◆ 10kg Of Cement (White & Gray As Per Requirement) , 5 Kg Free Flow Fine Plaster Sand And 200ml To 300ml Of Liquid Super Tile Adhesive Chemical

For Flooring Area :- In Case Affixing Tiles, Granite & Marble In Flooring Area So Prefere This Mix Ratio

◆ 10kg Of Cement (White & Gray As Per Requirement) , 10 Kg Free Flow Fine Plaster Sand And 200ml To 300ml Of Liquid Super Tile Adhesive Chemical

For Example:- We Are Preparing Mortar For Tiles & Granite Installation With First Mix Ratio In Case Of Affixing Granite Slabs, Ceramic Tiles , Vitrifide Tiles Or Natural Marble Slabs On Concrete Wall, Blend 200ml To 300ml Of Siddhi Vinayak Liquid Super Tile Adhesive With 10 Kg Cement (White Or Gray As Per Requirement), 2/3 Liters Of Water And 05 Kg Free Flow Fine Plaster Sand Than Mix Well To Prepare Thick Mortar.

Prepare The Mortar Using 1 Liter Of Super Tile Adhesive While Maintaining The Same Mix Ratio.” The Prepared Mortar Can Be Used For Fixing Tiles Over 160 Sq.Ft./Ltr. To 175 Sq.Ft./Ltr. Depending On Wall Surface Finish Area And By Forming 8 Mm To 10 Mm Thick Bed . Smear The Mortar On Floor Surface Uniformly And Compress The Marble, Granite And Ceramic Tiles To Fix These In Desired Position. Apply The Mortar On Primer Treated Mosaic Floor In A Uniform Manner. Position The Slab Or Tile To Their Precise Position On The Mortar Treated Surface. It Should Be Remembered That Primer (Applied By Brush) Tends To Dry Within Short Period. Therefore, The Primer Needs To Be Applied On Marble Or Granite Or Tile Shortly Before Their Affixing.

Standards

- IS 9103:1999
- ASTM C 494

PACKAGING

Packing Size : - 5ltr, 10ltr, 20ltr Bucket

Packing Material : - HDPE Buckets



5Ltr.



10 Ltr.




20 Ltr.

Manufactured & Marketed by :

SIDDHI VINAYAK

CONSTRUCTION CHEMICAL PVT. LTD.

Corporate Office : S.V. House No. 2, Opp. Shri Ramsharnam Road
Ward No. 22, Utaili, Satna, Pin - 485001, M.P India.

 **+91-9713958888**

 **info@svccpvtltd.com, query@svccpvtltd.com**

 **svccpvtltd.com**

tollfree 18008902498