



SIDDHI VINAYAK CONSTRUCTION CHEMICAL PVT. LTD.

CLEAR COATTM

WATER REPELLENT AGENT

सिद्धिविनायक का वादा..
मजबूती सबसे ज्यादा...



About

Clear coat is coating material, also known as acrylic polymer, and is widely available. Commonly chosen as a substitute for water repellent on concrete surface.

Description

Clear coat is a high gloss clear fast drying, flexible, protective, and insulating coating designed to protect concrete substrates from atmospheric corrosion, dust, and other common contaminants. Clear Coat is also transparent paint that goes over your base coat and protects it from damage and UV rays. It also gives a glossy finish that deepens the base colour quality and lets you easily buff out small scratches. Clear Coat is less resistant to oxidation and fading.

Advantages

- Quick drying, glossy, clear/transparent & flexible coating.
- Forms a tough anti-corrosion, moisture proof, non-reactive protective coating.
- Provides insulation film on surfaces to which applied.
- Provides long term protection.
- White spathes will be reduced from surface area.
- Free from ozone depleting substances.

Application & Precautions - :

- Cleaning - : Ensure surface is dust-free and dry ,
- Recommended Tools - : Use brush, roller, sponge, low pressure spray gun.
- Finish- : Apply only 1 coat and get the best high sheen finish than as per required
- Dry Time- : Maximum take a time for dry 30 to 45 minutes depending on weather condition
- Protective- : Keep out of sunlight, ensure ventilation and Avoid moisture during application
- Average Coverage- : Coverage Rates Of 12 M² to 15 M² Per Liter Will Be Obtainable.
- Decorative tiles, Flooring concrete Parking tiles, Wall tiles, Paver block, interlocking tiles, Industrial flooring Etc.



Using Process

The surface area should be dry and clean. Clear Coat water replant agent is applied in thin layers, covering the complete surface. Application by a brush, roller or cloth is also possible. Depending on the porosity and texture of the concrete surface, typical coverage rates of 8 to 10 m² per litter will be obtainable.

Precaution and Limitations

- Exhaust Fans- : Consider using exhaust industrial fans for larger areas to ensure adequate ventilation.
- Keep out of reach of children ,
- Respirators - : Protect against inhaling harmful paint fumes and airborne particles,
- Gloves - : Prevent skin irritation or chemical burns from direct contact with the paint,
- Safety Goggles - : Shield eyes from paint splashes and aerosols.
- Protective Clothing - : Coveralls or old clothes that can be discarded to prevent staining
- Clear coat shall not be added to directly cement, do not apply Clear Coat on moist substrates. Freshly applied Clear Coat must be protected from damp, condensation, and water for at least 12 hours.

PACKAGING

Packing Size :-
2.5 Ltrs, 50 Ltrs, 200 Ltrs

Packing Material :-
HDPE Cane, HDPE Jar
HDPE Barrel



2.5 Ltrs.



50 Ltrs.



200 Ltrs.



Manufactured & Marketed by :

SIDDHI VINAYAK

CONSTRUCTION CHEMICAL PVT. LTD.

Corporate Office : S.V. House No. 2, Opp. Shri Ramsharnam Road
Ward No. 22, Utaili, Satna, Pin - 485001, M.P India.

 **+91-9713958888**  **info@svccpvtltd.com, query@svccpvtltd.com**

 **www.svccpvtltd.com tollfree 18008902498**

