SIDDHI VINAYAK
CONSTRUCTION CHEMICAL PVT. LTD.

ACRYLIC™
Floor Guard

Non Scratchable Durable Coat



ISO 9001 2015 CERTIFIED

सिद्धिविनायक का वादा..
मजबूती सबसे ज्यादा...

Description

®SVCC acrylic floor guard is hard wearing. premium- quality solvent-based floor paint with a high-sheen finish for the decorative, along with protection of cement concrete articles, like a paver blocks, Checkered tiles , parking tiles , and concrete floors. Etc.

®SVCC acrylic floor guard specially formulated to resist scratches , stains and wear - ideal for high - traffic areas like garages shops and industrial floors ,and Resistant to petrol, oil, salt water and light rubber-wheeled vehicular traffic. ®SVCC acrylic floor guard only concrete floors For interior and exterior use. Not suitable for asphalt.

Key Features

- Reduced Maintenance Costs ,
- High-sheen Finish ,
- Slip Resistance ,
- Scratch & Abrasion Resistant ,
- Increased Property Value ,
- Weather & Water Resistant ,
- Resistance to Stains ,
- Non-Porous Surface ,
- Enhanced Aesthetics ,
- Protection and Durability
- Easy Maintenance and clean ,

Application & Precautions - :

- Cleaning - : Ensure surface is dust-free and dry ,
- Recommended Tools -: Use brush, roller, sponge, low pressure spray gun.
- Finish- : Apply only 1 coat and get the best high sheen finish than as per required ,
- Dry Time - : maximum take a time for dry 30 to 45 minutes depending on weather condition ,
- Protective -: Keep out of sunlight , ensure ventilation and Avoid moisture during application
- Average Coverage -: Coverage Rates Of 12 M^2 To 15 M^2 Per Liter Will Be Obtainable.
- Decorative tiles ,Flooringconcrete, Parkingtiles, Walltiles, Paverblock, Interlockingtiles, Industrial flooring Etc.

Precaution and limition -:

- Exhaust Fans- : Consider using exhaust industrial fans for larger areas to ensure adequate ventilation.
- Keep out of reach of children ,

- Respirators - : Protect against inhaling harmful paint fumes and airborne particles,
- Gloves - : Prevent skin irritation or chemical burns from direct contact with the paint,
- Safety Goggles - : Shield eyes from paint splashes and aerosols.
- Protective Clothing - : Coveralls or old clothes that can be discarded to prevent staining or chemical exposure.
- Keep away from heat or fire when applying ,

Availability of Shades

- Red
- Pencil Grey
- Yellow
- Dark Brown
- Silver Grey
- Z-black

PACKAGING

Packing Size : -
20 Ltr.
Tin Container



Manufactured & Marketed by :

SIDDHI VINAYAK
CONSTRUCTION CHEMICAL PVT. LTD.

Corporate Office : S.V. House No. 2
Opp. Shri Ramsharnam Road, Ward No. 22
Utaili, Satna, Pin - 485001, M.P India.

+91-9713958888 www.svccpvtltd.com

info@svccpvtltd.com, query@svccpvtltd.com

tollfree 18008902498

